

ONE TOUCH FITTINGS

Series WP2

Cat No WP2 - 01 - D

Nylon Tube



| Tube OD in mm | Ø4 | Ø6 | Ø8 | Ø10 | Ø12 | Ø14 |
|-----------------|---------|---------|---------|---------|---------|---------|
| Ordering no. | WH01W04 | WH01W06 | WH01W08 | WH01W10 | WH01W12 | WH01W14 |

Colour: Nylon-White

Usage instructions

(For maximum efficiency)


- ☐ Cut the tube end burr free and square, using **Tube cutter (WC1)** and clean the edge to ensure leak tight joints. (Do not use blunt tools / hacksaw / chisel etc,.)
- ☐ Ensure the tube is fully inserted into the fitting until the positive stop, beyond the 'U' seal.
- ☐ Tightening torque for threaded components

| Thread size | Tightening torque Nm |
|-------------|----------------------|
| M5 | 1 - 1.5 |
| 1/8 | 7 - 9 |
| 1/4 | 12 - 14 |
| 3/8 | 22 - 24 |
| 1/2 | 28 - 30 |

☐ Minimum bend radius of the tubing to avoid leakage

| Min. bend radius | OD of tube | Ø4 | Ø6 | Ø8 | Ø10 | Ø12 | Ø14 |
|------------------|------------|----|----|----|-----|-----|-----|
| for (in mm) | Nylon | 15 | 40 | 50 | 60 | 80 | 100 |

Tube Cutter



| Ordering No | WC1 | | |
|-------------|-----|--|--|
| | | | |

Can cut tubes upto Ø12mm OD

How to Order

While ordering fittings, mention the Ordering number given in the corresponding tables, and for tubes, mention the ordering number with required length in metres.